

STL9961

AMENDMENTS

1. (Original) A method to determine a time domain equalized signal-to-noise ratio of a mass storage device, the method comprising the steps of:

- (a) retrying verification of read data at a phase level; and
- (b) retrying a time domain equalized signal-to-noise ratio at a global level.

2. (Original) The method of claim 1, wherein the retrying step (a) further comprises the steps of:

- (a)(1) verifying all phases of the read data;
- (a)(2) determining a qualification of all phases of the read data; and
- (a)(3) determining exhaustion of phase level retry.

3. (Original) The method of claim 1, wherein the retrying step (b) further comprises the steps of:

- (b)(1) comparing the time domain equalized signal-to-noise ratio to a predetermined threshold; and
- (b)(2) determining the exhaustion of global level retry.

STL9961

4. (Original) The method of claim 1, wherein the method further comprises the steps of:

- (c) filling a write buffer of the mass storage device with data, the data having a pseudo-random pattern;
- (d) setting a read channel of the mass storage device to output sampled analog-to-digital converted data to a NRZ bus of the mass storage device;
- (e) writing the write buffer to a media of the mass storage device; and
- (f) reading all phases of the data stored on the media, yielding read data.

5. (Original) The method of claim 4, wherein the filling step (c) is performed after the setting step (d).

6. (Original) The method of claim 4, wherein the filling step (c), the setting step (d), and writing step (e) and the reading step (f) are performed after the retrying step (a).

7. (Original) The method of claim 4, wherein the method further comprises the step of:

- (g) calculating a time domain equalized signal-to-noise ratio from the read data.

8. (Original). The method of claim 7, wherein the calculating step (g) is performed after the retrying step (a), and before the retrying step (b).

9. (Original) The method of claim 7, wherein the method further comprises the step of:

- (h) determining that the mass storage device passed or failed.

STL9961

10. (Original) The method of claim 1, wherein the mass storage device further comprises a disc drive.

11. (Currently Amended) ~~A disc drive to perform a manufacturing quality assurance pass/fail test on an electronic device, the disc drive comprising:~~

a base;

a disc rotatably attached to the base;

an actuator for carrying a transducer head in a transducing relation with respect to the disc; and

a disc drive controller, communicatively coupled to the actuator,

operably programmed to:

retry verification of read data at a phase level; and

retry a time domain equalized signal-to-noise ratio at a

global level, which further includes:

~~a determiner of a time domain equalized signal-to-noise ratio~~

~~of the disc, the disc drive controller operably coupled~~

~~to the disc.~~

12. (Canceled)

13. (Canceled)

STL9961

14. (Currently Amended) The disc drive of claim ~~11~~ 13, wherein the controller phase-level retriever is further programmed to comprises:

verify all phases of the read data;

determine a qualification of all phases of the read data; and

determine exhaustion of phase level retry.

~~a read-data phase verifier;~~

~~a qualification determiner, operably coupled to the global level
retriever; and~~

~~a phase level completion determiner, operably coupled to the
qualification determiner.~~

15. (Currently Amended) The disc drive of claim 14, wherein the controller global-level retriever is further programmed to comprises:

compare the time domain equalized signal-to-noise ratio to a
predetermined threshold; and

determine the exhaustion of global level retry.

~~an ESNR threshold determiner; and~~

~~a global level completion determiner, operably coupled to the ESNR
threshold determiner.~~

16. (Original) The disc drive of claim 11, wherein the disc drive further comprises a magnetic disc drive.

17. (Original) The disc drive of claim 11, wherein the disc drive further comprises an optical disc drive.

STL9961

18. (Currently Amended) A method to test a mass storage device, the method comprising the steps of:

- 23
- (a) downloading Equalized Signal-to Noise Ratio (ESNR) ~~ESNR~~ determining firmware to a memory of the mass storage device;
 - (b) determining an ESNR value of the recording medium of the mass storage device, by ~~executing~~ performing the ESNR determining firmware; and
 - (c) determining rejection or acceptance of the recording medium of the mass storage device, from the ESNR value.

19. (Original) The method of claim 18, wherein the determining step (b) further comprises:

- (b)(1) performing the ESNR determining firmware, yielding an ESNR value.

20. (Original) The method of claim 18, wherein the mass storage device further comprises a disc drive.

21. (Currently Amended) An information handling system comprising:

a mass storage device;

~~— a base;~~

~~— a disc rotatably attached to the base;~~

~~an actuator assembly movably attached to the base the actuator assembly further comprising a voice coil attached to the actuator assembly;~~

~~— a processor operably coupled to the actuator; and~~

~~a means operative on the processor to determine a time domain phase level retry and global level retry of an equalized signal-to-noise-ratio of the~~ mass storage device ~~disc.~~

STL9961

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (New) An apparatus configured to perform the method of claim 1.

26. (New) The apparatus of claim 25, further comprising:
a data storage disc; and
a controller, communicatively coupled to the data storage disc,
operably programmed to:
retry verification of read data at a phase level; and
retry a time domain equalized signal-to-noise ratio at a
global level.
